

# Excel in Your Field™

## Specifications

CATEGORY	MT573C	MT573CPS
<b>ENGINE</b>		
Type	4 Cylinder, CRDI, Water-cooled	
Model	L4C25-T	
Emission	Tier4 Final	
Engine HP, kW	73 (54.4)	
PTO, HP	62	
Rated speed, rpm	2,500	
Displacement, in <sup>3</sup>	152.9	
Fuel tank capacity, gal	26.4	
<b>DRIVE TRAIN</b>		
Transmission type (option)	Synchro Shuttle	Power Shuttle
No. of speed	F20 x R20	
Forward speed, mph	0.12 ~ 20.6	
<b>PTO</b>		
Type	Independent	
Rear, rpm	540 / 750 / 1,000	
<b>HYDRAULIC SYSTEM</b>		
Control system	Position / Draft	
Implement pump, gpm	13.2	
Steering pump, gpm	6.6	
Total flow, gpm	19.8	
Category, 3pt hitch	CAT II	
Hitch lift capacity, lbs	6,614	
Remote ports	3 pairs (Front), 3 pairs (Rear)	
<b>DIMENSION</b>		
Overall length, Frame to link, in	150	
Overall width with tires, in	74.4	
Wheelbase, in	84.6	
Height to top, in	104.4	
Total weight without ballast, lbs	6,620	6,669
<b>TIRE SIZE</b>		
Front	11.2 - 24	
Rear	16.9 - 30	

Note Specifications and design are subject to change without prior notice.

### Get More Standard Features

- Power & tilt steering
- Switch operated Independent PTO
- Front loader valve and 3rd function joystick
- Deluxe adjustable seat
- Remote control valves (3 pair)
- Rear work light
- Horn
- Deluxe cab with AC and heat
- Cabin air recirculation
- Front & rear windshield washer/wipers
- Deluxe stereo system with CD player
- 7 pin electrical connector
- Draw bar
- Hydraulic draft & position control with auto lift
- Pre-heat starting aid
- Hand & foot accelerator control
- Safety flashers & turn signals
- Fuel, coolant temperature, tachometer & hour meter gauges
- Differential lock, parking brake, battery charging, engine oil pressure, fuel filter, hydraulic oil filter pressure, 4WD, PTO operation, high beam operation / warning lights

Front end Loader	LL6100
<b>Tractor Application</b>	
Bucket Size, in.	78
Maximum Lift Height, in.	126.5
Clearance with Attachment Dump, in.	95.3
Reach at Maximum Height, in.	5.7
Maximum Dump Angle, deg.	64
Maximum Rollback Angle, deg.	38
Digging Depth, in.	7.0
Overall Height in Carry Position, in.	64.2
Lift Capacity (@ Pivot pin), lbs.	3,626
Breakout Force (@ Pivot pin), lbs.	6,644
Approx. Weight (Loader w/o Bucket), lbs.	1,232



# LS Tractor USA

LS Tractor USA | 6900 Corporation Parkway, Battleboro, NC  
 P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

Dealer Imprint Zone