

# 2011 NEW PRODUCT

Pursue your passion



## P-Series P7010C P7030C P7030 CPS P7040 CPS

<b>ENGINE</b>				
Type	4 - Cylinder, Direct - injection, Water - cooled			
Model (Tier 3)	Iveco FPT F5C		Iveco FPT NEF	
Engine HP (Gross)	72	88	88	97
PTO HP	63	77	77	85
Rated speed, RPM	2300			
Displacement-cu, In.	195.3 + TC	195.3 + TCA	273.4 + TCA	
Fuel tank capacity (gal)	26.4			
Alternator	12V - 120 Amps		12V - 90 Amps	
<b>DRIVE TRAIN</b>				
Transmission	Synchro shuttle		Power Shuttle with hi - low	
No. of Speeds with creeper	20F / 20R		40F / 20R	
Brakes	Wet, Multi - disc			
Steering	Hydrostatic Power Steering			
<b>PTO</b>				
Type	Full Independent or Manual			
Rear(rpm)	Standard(540/750/1000 rpm)			
PTO function	Shiftable ground speed PTO			
<b>HYDRAULIC SYSTEM</b>				
Implement pump, gpm	12.0		15.9	
Steering pump, gpm	7.0		7.0	
Total flow, gpm	19.0		22.9	
Category, 3pt hitch	CAT 2		CAT 2	
Hitch Lift capacity, lbs	6173		6173	
Lift control type	Position / Draft			
<b>DIMENSIONS</b>				
Overall length with 3pt, in.	157.1	157.1	160.5	
Min. overall width with Ag tires, in.	77.8	79.5	78.7	
Wheelbase, in.	86.6	86.6	90	
Ht to top of cab. with Ag tires, in.	102.3	103.5	103.9	
<b>TIRE SIZE</b>				
Ag Front	11.2 - 24	12.4 - 24	13.6 - 24	
AG Rear	16.9 - 30	18.4 - 30	18.4 - 34	
IND and Turf	N/A			
<b>WEIGHT</b>				
Total weight without ballast, lbs	6675	6724	7143	

Note Specifications and design are subject to change without prior notice.

## Implement

Tractor Application	LL7100	LL7101
	P7010C/P7030C / P7030 CPS	P7040 CPS
Maximum Lift Height, in.	135	136.4
Clearance with Attachment Dump, in.	100.6	101.6
Reach at Maximum Height, in.	23	20
Maximum Dump Angle, deg.	47	47
Maximum Rollback Angle, deg.	50	50
Digging Depth, in.	6.1	5
Overall Height in Carry Position, in.	69.7	70.8
Lift Capacity (@ Pivot Pin), lbs.	3500	3500
Breakout Force (@ Pivot pin), lbs.	5088	5088
Approx. Weight (Loader w/o Bucket), lbs.	1892	1984

## Standard Equipment

- Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control
- Instrumentation-alternator
- Warning and engine oil pressure light
- Remote-control valve (3 pairs)
- Hydrostatic & tilt power steering
- Front outlet valve and loader joystick
- Hydraulic draft and position control
- Rear working light
- Adjustable seat
- Telescopic stabilizer & Drawbar
- Safety flashers
- Turn signals
- Ground speed PTO
- Automatic lift arm
- Standard 7 pin implement light socket
- Extendable lift arms
- Deluxe cabin with Heating and A/C
- Cabin air recirculation, interior lighting
- Front & Rear windshield washer/wiper system
- Deluxe Stereo system with CD Player

Dealer Imprint Zone