

TEM	REMARK
ENGINE	
Manufacturer	Caterpillar
Model	C2.2
Engine hp. Gross (kw)	42.7 (31.4)
PTO Horsepower (kw)	32.8 (24.1)
Rated engine speed	2600
Number of cylinders	4
Dispalcement-in. (cc)	135.2 (2216)
Air cleaner	Dual Dry
ELECTRICAL SYSTEM:	
Alternator	12V, 65A
Starter Motor	-
FUEL SYSTEM:	
Type	Indirect Fuel Injection
Fuel	-
Fuel Tank, US gal. (L)	17(60)
DRIVETRAIN	
Transmission type	Sync/Shuttle
Number of speeds	16/F 16/R
Max. traveling speed, mph (km/h)	19.7(31.7)
Brakes	Wet Disc
4WD (MFWD)	-
Steering	Hydrostatic power
Clutch	Dry Single Plate
HYDRAULIC SYSTEM	
Pump (type)	Dual Gear Pump
Implement pump cap.gpm (L/min)	8.8(33.5)
Steering pump cap. gpm (L/min)	4.6(17.6)

Maximum total flow gpm (L/min)	3.4(51.1)
Lift control type	Position/Draft
Hitch lift capacity at 24 inches behind link ends, lb(kg)	2945 (1336)
Aux. Hydraulics	-
Hitch lift capacity, lb. (kg)	3313(1503)
Single Lever Joystick & Control Valve	Standard
Category, 3 point hitch	Cat. I
PTO	
Rear (rated eng. rpm)	540
Mid (rated eng. rpm)	N/A
Type	Independent
Rotation Direction	-
Clutch	-
Control	Electric/Hydro
Shaft Diameter in. (mm)	1 3/8 (35)
DIMENSIONS(with standard tires)	
Overall length, in. (mm) with 3P	141.3(3590)
Overall width, in. (mm)	72.3(1837)
Height to top of ROPS, in. (mm)	101.9(2590)
Wheelbase, in. (mm)	76.2(1935)
Min. Ground Clearance, in (mm)	13.8(350)
Weight, lb. (kg)	4188(1900)

Min. Turning Radius, in (mm) with brakes	131.9(3352)
Min. Turning Radius, in (mm) w/o brakes	150.4(3820)
Tyre Size (Standard)	
Front	8-16 R1
Rear	13.6-24 R1
ROPS	
Standard	ROPS
CAPACITIES	
Cooling System U.S. qt. (L)	9.0(8.5)
Crankcase (with filter) U.S. qt. (L)	8.4(8.2)
Trans. & Hydr. System, U.S.gal. (L)	9.2(35)
Front Axle qt. (L)	10.5(10)