



SPECIFICATIONS

CATEGORY					
ENGINE	MT458	MT458CPS	MT468	MT468C	MT468CPS
Type	4Cylinder In-line Vertical, Water-cooled 4cycle Turbo Diesel, CRDI				
Model (Tier 4)	L4C25-T				
Engine HP (gross)	58			68	
PTO (HP)	51.2			60	
Rated Speed (rpm)	2,500				
Displacement (in ³)	152.8				
Fuel Tank Capacity (gal.)	21.1				
Alternator (V-A)	12-70				
DRIVE TRAIN					
Transmission	Synchro Shuttle / Power Shuttle (CPS Models)				
No. Of Speed	F16 x R16				
Brakes	Wet, Multi-disc				
PTO					
Type	Independent				
Rear (rpm)	540				
HYDRAULIC SYSTEM					
Control System	Position / Draft				
Implement Pump (gpm)	9.9				
Steering Pump (gpm)	4.6				
Steering	Hydrostatic Power Steering				
Total Flow (gpm)	14.5				
Category (3pt Hitch)	CAT II				
Hitch Lift Capacity (Hitch End) (lbs.)	4,079				
Remote Valves	2 Pairs Standard				
DIMENSION					
Overall Length (Bumper To Link in.)	138.6				
Overall Width With Tires (in.)	70				
Wheelbase (in.)	80.3				
Height To Top Of ROPS (in.)	103	100.6	103		100.6
TIRE SIZE					
Front / Rear Ag	9.5 - 20 / 16.9 - 24				
Front / Rear Industrial	10.5 / 80 - 18, 19.5L - 24				
Front / Rear Turf	36 x 13.5 - 15, 16.9 - 24				
WEIGHT					
Total Weight w/o Ballast (lbs.)	4,674	5,121	4,674		5,121

Note specifications and design are subject to change without prior notice.

FRONT END LOADER		LL5106
TRACTOR APPLICATION		MT4 SERIES
Bucket Size (in.)		72
Maximum Lift Height (in.)		116.3
Clearance With Attachment Dump (in.)		82.8
Reach At Maximum Height (in.)		6.6
Maximum Dump Angle (deg.)		72
Maximum Rollback Angle (deg.)		46
Digging Depth (in.)		4.2
Overall Height In Carry Position (in.)		68.9
Lift Capacity (At Pivot Pin) (lbs.)		2,981
Breakout Force (At Pivot Pin) (lbs.)		4,767

BACKHOE		LB3102
TRACTOR APPLICATION		MT4 SERIES
Digging Depth (in.)		94.5
Reach From Centerline Of Swing Pivot (in.)		136.2
Loading Height (in.)		80.3
Swing Arc (deg.)		180
Transport Height (in.)		92.9
Bucket Rotating (deg.)		180
Stabilizer Spread (Down Position) (in.)		68.7
Stabilizer Spread (Up Position) (in.)		46.5
Bucket Digging Force (lbs.)		3,740

Additional Equipment Available

- Deluxe Cabin With Heating & A/C
- Cabin Air Recirculation
- Front & Rear Windshield Washer/Wiper System (Cab On)
- Deluxe Stereo System With CD Player, USB (Cab On)
- Pre-heat Starting Aid
- Hand & Foot Throttle Control
- Tilt Steering
- Front Loader Valve And Joystick
- Hydraulic Draft & Position Control
- Adjustable Seat
- Lower Links & Telescopic Stabilizers
- Drawbar
- Flashers
- 7-Pin Implement Socket